



Report No.: RSZBHST230106046-2 Date of Issue: Jan.09 2023

Approved by 批准: Ayvin

#### 1. PRODUCT AND COMPANY IDENTIFICATION 产品和企业标识信息 Product Detail 产品详情 Product Name: Camera Li-ion Battery 产品名称: 摄像机锂离子电池组 Model: BIVO-98 型목: Manufacturer Name: SWIT Electronics Co.,Ltd. 生产商名称: 南京奥视威电子科技股份有限公司 10 Heng Tong Road, Xin'gang Nanjing Economic and Manufacturer Address: Technological Development Zone Nanjing 210038, P.R. China 生产商地址: 江苏省南京经济技术开发区恒通大道 10号 Manufacturer E-mail: zh@softorange.cn 生产商邮箱: Manufacturer Pos code: 210000

### 2. HAZARDS SUMMARIZING 危险性概述

86-13851773361

Classification of Danger: (see section 14)

telephone

危险类别: (见第十四部分)

生产商邮编:

紧急联系号码:

Emergency number:

Invasion Route: eyes, skin contact, ingestion

侵入途径:眼睛、皮肤、食入

Health Hazard: the lithium ion batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of rupture, fire, heat, leakage of internal components, with could cause casualty loss. Abuses include but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.

健康危害:正常条件下根据制造商的说明使用锂离子电池不会产生危害。使用不当的情况下,有破裂、火灾、热、内部成分的漏出的风险,并可能造成意外损失。使用不当的行为包括但不限于下列情况:长时间充电、短路,投入火灾,硬物撞击、尖物刺破、破碎、破裂。

Environmental Hazard: Not reported

环境危害:未见报道

The Danger of Burning and Exploding: May occur fire or explosion in high temperature



or short circuit.

燃爆危险:高温或短路条件下可能会引发火灾或爆炸

### 3. COMPOSITION / INFORMATION ON INGREDIENTS 成分及组成信息

Pure chemical	Mixture∑
纯品: □	混合物⊠

化学组成:

Chemical ingredients:

Ingredient Name 成分名称	CAS No. CAS号(化学文摘索引登 记号)	Percent of Content (%)含量百分比
Positive electrode:	12190-79-3	20~60
Lithium transition metal	12031-65-1	
oxidate(Li[M]m[O]n*2)	12057-17-9	
	182442-95-1	
	207803-51-8	
Positive electrode's base:	7429-90-5	1~10
Aluminum		
Negative electrode:	7782-42-5	10~30
Carbon	7440-44-0	
Negative electrode's base:	7440-50-8	1~15
Copper		
Electrolyte:	623-53-0	5~25
Ethyl methyl carbonate	105-58-8	
Diethyl carbonate	96-49-1	
Ethylene carbonate	21324-40-3	
Lithium hexafluorophosphate		
Outer case:	7429-90-5	1~30
Aluminum, Iron, aluminum	7439-89-6	
laminated plastic		

Note 注:

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CAS 号是化学文摘服务注册号



4. FIRST-AID M	EASURES 急救措施
Eyes:	Irrigate thoroughly with water for at least 15 minutes. Obtain
Lyes.   眼睛:	medical attention.
山区中日・	用水彻底冲洗至少 15 分钟。迅速就医。
Skin:	Wash off skin thoroughly with water. Remove contaminated
皮肤:	clothing and wash before reuse. In severe cases obtain medical
1×11×.	attention.用水彻底冲洗皮肤。 脱去污染的衣服,并在重新使用前清
	洗。 在严重的情况下迅速就医。
Inhalation:	Remove from exposure, rest and keep warm. In severe cases
W入:	obtain medical attention.
<b>ラ</b> 及ノへ・	暴露,休息和保暖。在严重的情况下迅速就医。
Ingestion:	Wash out mouth thoroughly with water and give plenty of water to
·····································	drink. Obtain medical attention.
1双/八	用水彻底冲洗口腔,并喝足够的水。迅速就医。
	All cases of eye contamination, persistent skin irritation and
Further	casualties who have swallowed this substance or been affected by
treatment:	breathing its vapours should be seen by a Doctor.
进一步治疗:	医生应该看到所有眼睛污染,持续性皮肤刺激和吞咽这种物质或受
	到蒸气呼吸影响的人员。

5. FIRE-FIGHTING MEASURES 消防措施		
Characteristics of Hazard 危险特性:	Toxic fumes; gases or vapors may evolve on burning. 在灭火时可释放有害浓烟、气体或者蒸汽。	
Hazardous Combustion Products: 有害燃烧产物:	When burned, hazardous products of combustion including fume of carbon monoxide and carbon dioxide can occur. 燃烧时,会产生包括一氧化碳和二氧化碳的燃烧的有害燃烧物。	
Extinguishing Media: 灭火介质:	Water, carbon dioxide, dry chemical or foam. 水,二氧化碳,干化学品或泡沫。	
Basic Fire Fighting Procedures: 基本消防程序:	Wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.  佩戴 NIOSH / MSHA 认可的正压自给式呼吸器和防护服,以防止接触皮肤和眼睛。	

6. ACCIDENTAL RE	ELEASE MEASURES 泄露应急处理
	If the battery breakage and electrolyte leakage, evacuate



	personnel until the smoke cleared.
Accidental:	如果电池破损和电解液泄漏,疏散人员直到烟雾消失。
非主要的:	Wipe with a cloth and placed in steel drums into the bag inside.
	If the battery is hot, away from the scene firstly, cool the battery,
	so that the steam dissipated. Adequate ventilation.
	用布擦拭,然后将钢桶放入袋内。如果电池很热,请先离开现场,
	冷却电池,使蒸汽消散。 通风良好。
	Avoid skin or eye contact steam.
	避免皮肤或眼睛接触蒸汽。
Waste treatment:	The battery Should discharge completely, the waste batteries
废物处理:	will be turned over in the relevant sector, and all waste must
	refer to the United Nations, national, local regulations for
	disposal. Reference to national or federal Environmental
	Protection Agency EPA.
	电池应完全放电,废电池将在相关部门翻转,所有废物必须参考
	联合国,国家和地方的处置规定。 参考国家或联邦环境保护局
	EPA <sub>°</sub>

### 7. HANDLING AND STORAGE 操作处置与储存

Prohibit mechanical or electrical damage battery.

禁止机械或电气损坏电池。

Stored in a dry, cool and ventilated environment, to avoid temperature changes or high temperature.

储存在干燥,阴凉,通风的环境中,避免温度变化或高温。

Keep away from heat, avoid prolonged sun exposure.

远离热源, 避免长时间暴露在阳光下。

Against short circuit, overcharge, forced discharge, or in a fire.

防止短路, 过充电, 强制放电或发生火灾。

Battery disassembly, crush, fire or high temperatures can cause fire or explosion, prohibit short-circuit or error operation.

电池拆卸,挤压,着火或高温可能引起火灾或爆炸,禁止短路或误操作。

8.EXPOSURE CONTROLS / PERSONAL PROTECTIO 接触控制/个体防护		
Respiratory protection:	If the battery leaks, the need for full ventilation.	
呼吸系统防护:	如果电池漏液,需要充分通风。	
Hand Protection:	Under normal use, do not.	
手部防护:	在正常情况下不需要。	
Personal Protection:	Under normal use, do not.	
个人防护:	在正常情况下不需要。	



Other protection:Under normal use, do not.其他保护:在正常情况下不需要。

If the battery leaks, must wear the following protection products.

如果电池漏液,必须佩戴以下保护产品:

	Respiratory Protection 呼吸系统防护	In all fire situations, use self-contained breathing apparatus. 在所有火灾情况下,请使用自给式呼吸器。
m m	Hand Protection 手部防护	In the event of leakage wear gloves. 在发生泄漏时戴上手套。
	Eye Protection 眼睛保护	Safety glasses are recommended during handling. 处理过程中建议使用安全眼镜。
	Other 其他	In the event of leakage, wear chemical apron. 如果发生泄漏,请穿化学防护。

9. PHYSICAL AND CHEMICAL PROPERTIES 理化特性		
Nominal Voltage: 标称电压	14.4V/28.8V	
Capacity: 容量	6.8Ah/3.4Ah	
Watt-hour: 瓦时	98.0Wh	
Appearance characters:	Black almost cuboid	
外观:	黑色近长方体	
Form:	Solid	
物理形态:	固态	

### 10. STABILITY AND REACTIVITY 稳定性和反应活性

Product is stable under conditions described in Section 7. 产品在第七部分所诉的条件下稳定。

5 / 9

Phone: +86 755 8650 3482 Check: cs@hc-stc.net Website: http://wwwh.hc-stc.net Room 202, 2/F, Building F, HaoWei Industrial Park, QingSong West Road, PingShan District, Shenzhen, Guangdong, China/518000



Hazardous reactions may occur under some specific conditions.	
在某些特定条件下可能会发生危险反应。	
Conditions to avoid: 应避免的条件:	When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Avoid to be exposed to direct sunlight and high humidity. 当电池暴露在外部短路,压碎,改性,高于 100℃的高温时,它将成为发热和点火的原因。 避免暴露在阳光直射和高湿度的环境中。
Materials to avoid: 要避免的材料:	Conductive materials, water, seawater, strong oxidizers and strong acids. 导电材料,水,海水,强氧化剂和强酸。
Hazardous decomposition products: 危险分解物:	Acrid or harmful gas is emitted during fire. 火灾时会释放出刺激性或有害气体。

11. TOXICOLOGICAL	INFORMATION 毒理学资料
Primary irritant effect: 主要刺激作用:	None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrotic lung injury and membrane irritation.  无,除非电池破裂。 如果暴露在内部物质中,腐蚀性烟雾会对皮肤,眼睛和粘膜造成很大的刺激。 过度暴露可引起非纤维化肺损伤和膜刺激的症状。
Inhalation: 吸入:	Lung irritant. 呼吸道有刺激性。
Skin contact: 皮肤接触:	Skin irritant. 皮肤有刺激性。
Eye contact: 眼睛接触:	Eye irritant. 眼睛有刺激性。
Ingestion: 摄入:	Tissue damage to throat and gastro-respiratory tract if swallowed. 吞咽会对喉咙和胃肠道造成组织损伤。
Medical conditions generally aggravated by exposure: 暴露会加剧医疗条件:	In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur. 如果接触到内部物质, 可能会发生湿疹, 皮肤过敏, 肺部损伤, 哮喘和其他呼吸系统疾病。



### 12. ECOLOGICAL INFORMATION 生态学资料

Environmental Impact: 对环境造成的影响:

Proper use and disposal of the battery will not harm the environment.

Dispose of the battery, away from water, rain and snow. 正确使用和处理电池不会损害环境。处理电池,远离水,雨和雪。

### 13. DISPOSAL CONSIDERATIONS 废弃处置

Do not incinerate, or subject cells to temperatures in excess of 100℃. Such abuse can result in loss of seal, leakage, and/or cell explosion.

不要焚烧或使细胞温度超过 100℃。这种滥用可导致密封,泄漏和/或细胞爆炸的丧失。 Waste disposal must be in accordance with the applicable regulations. Disposal of the lithium ion battery cells should be performed by permitted, professional disposal page: firms knowledgeable in state or local requirements of hazardous waste treatment and hazardous waste transportation. Incineration should never be performed by battery but users, eventually by trained professional in authorized facility with proper gas and fume treatment.

废物处理必须符合适用法规。锂离子电池的处理应通过允许的专业处理页面进行:公司了解危险废物处理和危险废物运输的州或地方要求。 焚烧不应该由电池进行,而是由用户进行,最终由经过授权的设施中经过培训的专业人员进行适当的气体和烟气处理。 Deserted batteries could not be treated as ordinary trash. could not be thrown into fire or placed in high temperature. could not be dissected, pierced, crushed or treated similarly. Best way is recycling.

废弃的电池不能被视为普通垃圾。不能被扔进火里或被放置在高温下。不能被解剖,刺穿,压碎或类似处理。最好的方法是回收。

14. TRANSPORT INFORMATION 运输信息		
UN NO.	UN3480, UN3481	
UN 编号	UN3480, UN3481	
Proper Shipping	UN3480 PI965 Lithium ion Batteries	
Name	UN3481 PI966 Lithium ion Batteries packed with equipment	
运输专有名称	UN3481 PI967 Lithium ion Batteries Contained In Equipment	
	UN3480 PI965 锂离子电池	
	UN3481 PI966 锂离子电池和设备一起	
	UN3481 PI967 锂离子电池安装在设备中	
Labels for Package	Class 9	
包装标志	第9类	



1		
ICAO/IATA	Can be shipped by air in accordance with	DGR 64rd
	international Civil Aviation Organization (ICAO),	
	TI or International Air Transport Association	
	(IATA) DGR 64rd Packing Instructions Section	
	IB of 965 or Section II of 966 /967	
	appropriately . 可根据国际民用航空组织	
	(ICAO),TI 或国际航空运输协会(IATA) DGR 第	
	64rd 包装说明(PI)965 Section IB 或(PI)	
	966、(PI) 967 Section II 的相关规定空运。	
IMDG CODE	International Maritime Dangerous Goods Code	IMDG CODE
	under Special Provision188	(Amdt 40-20)
	《国际海运危险货物规则》(IMDG CODE)根据	
	特殊规定 188	
ADR	European Agreement concerning the	ADR 2022
	International Carriage of Dangerous Goods by	
	Road under Special Provision 188	
	《国际危险货物道路运输欧洲协定》(ADR)根据	
	特殊规定 188	
RID	Regulations concerning the International	RID 2022
	Carriage of Dangerous Goods by Rail under	
	Special Provision 188	
	《国际危险货物铁路运输欧洲协定》(RID)根据	
	特殊规定 188	

May be shipped without being declared as Class 9 dangerous goods, when meet to the requirements above.

当符合上述规定时,可不被申报为第9类危险品运输

### 15. REGULATORY INFORMATION 法规信息

《Dangerous Goods Regulation》

《危险物品规则》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《对危险货物运输的有关规定的建议》

《International Maritime Dangerous Goods》

《国际海运危险货物规则》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《危险品安全运输技术指令》

《Classification and code of dangerous goods》

《危险货物分类和品名编号》

OSHA Hazard Communication Standard Status

《职业安全卫生法》



Toxic Substances Control Act (TSCA) Status

《有毒物质控制法》

SARA Title III

《超级基金修正案和再授权法案 III(302/311/312/313)》

**RCRA** 

《资源保护及恢复法案》

In accordance with all Federal, State and Local laws

根据所有联邦、州和地方法律。

### 16. OTHER INFORMATION 其他信息

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

以上信息基于我们所知的数据,并且据信其数据是正确的。 由于此信息可能在我们无法控制的条件下应用,并且可能不熟悉,并且由于在此数据之后提供的数据可能建议修改信息,因此我们对其使用结果不承担任何责任。 提供此信息的条件是,收到该信息的人应自行确定材料是否适合其特定用途。

